



Vantaggi per il cliente

- Regolazione all'indietro tramite 2 batterie 9V
- Funzioni extra per la prota MFP
- Alimentazione di tensione esterna (18V) per sistemi di azionamento Okin
- Tasto pairing esterno per centraline Okin RF/BT
- Ulteriore illuminazione sottoletto, commutabile tramite elemento di comando RF Okin e smartphone / tablet
- Ulteriore porta MFP per collegamento di altri componenti/accessori Okin

Standard configurations

Dati sulle prestazioni

Tensione di entrata	29 V DC
Tensione di uscita	18 V/CC (2* 9V(6LR61))
Attivazione	tramite porta MFP ad es. HE150, OM4
Collegamento	Porta MFP integrata

Ulteriori dati

Colore della custodia	nero (RAL 9005)
Tipo di protezione	IP20
Umidità relativa dell'aria	30 - 75 %
Temperatura ambiente	da +10 a +40

POWER DOWN BOX




A Phoenix Mecano Brand

Page 3/3 - stand of 02/2020


POWER DOWN BOX




Vorderansicht



Seitenansicht



Draufsicht



Note: Responsibility for OKIN products when used for specific applications and for adherence to the appropriate guidelines, standards and laws is borne by the manufacturer of the complete system into which OKIN products are fitted. We accept no liability for the correctness.

DewertOkin GmbH • Weststraße 1 • 32278 Kirchlengern
Phone: +49 (0)52 23 / 9 79 -0 • Fax: +49 (0)52 23 / 7 51 82 • Email: info@okin.de • Internet: <http://www.okin.de>