



Page 1/3 - stand of 02/2020

Combining versatility and performance



Customer benefits

• Can be combined with Okin systems

Note: Responsibility for OKIN products when used for specific applications and for adherence to the appropriate guidelines, standards and laws is borne by the manufacturer of the complete system into which OKIN products are fitted. We accept no liability for the correctness.

## **TOPLINE D**



## Page 2/3 - stand of 02/2020

## **Standard configurations**

## Performance data


Controller	Cable handset for direct control	
Number of keys	6	
Function LED	No	
Integrated flashlight/torch	No	
Backlight / colour	No	
Housing colour	Housing colour (top/bottom) black/black	
Additional characteristics		
Protection degree	IP20	
Relative humidity	30 - 75%	
Ambient temperature	+10 - +40°C	

Note: Responsibility for OKIN products when used for specific applications and for adherence to the appropriate guidelines, standards and laws is borne by the manufacturer of the complete system into which OKIN products are fitted. We accept no liability for the correctness.





Page 3/3 - stand of 02/2020



Seitenansicht Side view

Note: Responsibility for OKIN products when used for specific applications and for adherence to the appropriate guidelines, standards and laws is borne by the manufacturer of the complete system into which OKIN products are fitted. We accept no liability for the correctness.